

designed for scientists



MVP 10 basic

/// Data Sheet

For dry, oil-free applications

- Slimline, compact design and long service life
- Straightforward servicing and simple maintenance
- Diaphragm pump that is highly resistant to chemicals as all parts that come into contact with gas are made of PTFE or PTFE compounds

Scope of delivery

•MVP 10 basic











- •Vacuum hose
- •Silencer
- •Y hose connector 8 mm









designed for scientists

Technical Data

Pump rate max. (50/60Hz) [m³/h]	1.7	
Pump rate max. (50/60Hz) [I/min]	28.3	
Final pressure [mbar]	7	
Final pressure with gas ballast [mbar]	15	
Suction levels	2	
Cylinder	2	
Connection diameter suction side [mm]	10	
Connection diameter pressure side [mm]	10	
Gas ballast valve	yes	
Input pressure [mbar]	7 - 1050	
Speed (50Hz) [rpm]	1380	
Speed (60Hz) [rpm]	1680	
Noise at low. pressure [dB(A)]	65	
Dimensions (W x H x D) [mm]	245 x 155 x 320	
Weight [kg]	11.5	
Permissible ambient temperature [°C]	10 - 40	
Permissible relative humidity [%]	80	
Protection class according to DIN EN 60529	IP 54	
Voltage [V]	230	
Frequency [Hz]	50/60	
Power input [W]	180	



