

## Product data sheet

# HT30-M1 High temperature circulator

2-zone technique for working temperatures up to 400 °C



### Product Features

- ✓ Self-optimizing ICC temperature controller
- ✓ Strong pumping capacity 18 l/min - 1.2 bar max
- ✓ Automatic air-purge allows easy filling
- ✓ Backlit interactive 4-line LCD display
- ✓ Electronic level indication
- ✓ Integrated programmer for 6 x 60 program steps
- ✓ Integrated programmer stores up to 6 profiles (60 sections each)
- ✓ High heating capacity for short heat-up times

## Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)

Heating capacity kW	3
Viscosity max. cSt	30
Pump capacity flow pressure l/min	14 ... 18
Pump capacity pressure bar	0.8 ... 1.2
Power consumption A	15
Voltage Tolerance %	230V   ±10

Order number including voltage version (230V/50Hz) 9800031.03

## Technical data

Available voltage versions

Order No. 9800031

Available voltage versions:

9800031.13 230V 60Hz (Nema N6-20 Plug)

9800031.03 230V 50Hz (Schuko Plug - CEE 7/4 Plug Type F)

## Electronics

Interfaces	Profibus optional, RS232, RS485, Standby-Input
External pt100 sensor connection	integrated
Integrated programmer	6x60 steps
Temperature control	ICC
Temperature display	LED
Temperature setting	Keypad

## Dimensions and volumes

Filling volume expansion vessel l	1
Internal usable expansion volume l	1.5
Weight kg	27
Total dimensions cm (W x L x H)	23 x 23 x 58
Filling volume l	2
Pump connections	M16x1 male

## Temperature values

Working temperature range °C <sup>1</sup>	+70 ... +400
Temperature stability °C	±0.01 ... ±0.1
Ambient temperature °C	+5 ... +40
Temperature display resolution °C	0.01

<sup>1</sup> Starting with a working temperature from 200 °C always use counter cooling.  
Bath fluids available for working temperatures up to +350°C.

## Other

Classification	Classification III (FL)
IP Code	IP 21

## All Benefits



### 100% Checked.

100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



### Green technology.

Development consistently applied environmentally friendly materials and technologies.



### Control of the external application

External Pt100 sensor connection for precise measurement and control directly in the external application



## JULABO. Quality.

Highest standards of quality for a long product life.



## Quick start.

Individual JULABO consultation and comprehensive manuals at your disposal.



## Satisfied customers.

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



## Services 24/7.

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at [www.julabo.com](http://www.julabo.com).