

0 175

Upper basket

for the optimum loading of laboratory glassware.





- Suitable for narrow-necked and laboratory glassware
- Vertical clearance: 170 mm mm*
- Equipped with connection for hot air drying
- Powder dispensing not possible
- * Depending on the laboratory glassware the max. vertical clearance can be lower

Duadwah saharany	
Product category	
Washer-disinfectors, laboratory	•
Machine affiliation	
PG 8535	
PG 8536	•
Product category	
Insert/module for narrow-necked glassware	<u>•</u>
Injector basket	
Upper basket	•
Product properties	
Material	Stainless steel
Colour	Stainless Steel
Maximum vertical clearance in mm	170
Area of application	
Reprocessing of laboratory glassware	•
Capacity	
Narrow-necked glassware [number]	33
Standard electrical connection	
Number of phases	0
Voltage in V	0-0
Frequency in Hz	0-0
Total rated load in kW	0.00-0.00
Fuse rating in A	0-0
Dimensions and weight	
External dimensions, net height in mm	412
External dimensions, net width in mm	475
External dimensions, net depth in mm	531
External dimensions, gross height in mm	270
External dimensions, gross width in mm	525
External dimensions, gross depth in mm	540
Net weight in kg	6.30
Gross weight in kg	7.20
Companion pack	
E 351 injector nozzle, Ø 4 mm, length 160 mm [number]	33
E 353 clip for injector nozzle E 351 [number]	33
, ,	