



EmStat³ and 3+[™]

potentiostats

Contents

EmStat3 and 3+ (Blue) potentiostats	2
Differences between regular EmStat model and EmStat Blue model	2
Supported techniques	3
Specifications of general parameters	4
System specifications	5
EmStat 3 and 3+	5
EmStat 3 and 3+ regular model	5
EmStat 3 and 3+ Blue model	5
Standard EmStat configuration	6
Standard EmStat Blue configuration	6
EmStat Blue accessories	7
MUX8-R2 or MUX16 multiplexer	7
Magnetic stirrer	7
LM35 temperature sensor	7
Differential Electrometer Amplifier (DEA)	8
EmStat: Embedded Potentiostat for OEM purposes	8
EmStat as OEM module	8

EmStat3 and 3+ (Blue) potentiostats

The EmStat and EmStat Blue instrument series are the smallest electrochemical interfaces available on the market. The devices are general purpose potentiostats but are also available as separate module for OEM use in specific applications.

EmStat is always shipped in a rugged carrying case. See also page 6.

Differences between regular EmStat model and EmStat Blue model

	EmStat ³ and 3+™	EmStat ³ and 3+ blue
		
Size (cm)	6.7 x 5.0 x 2.8	10.0 x 6.0 x 3.4
Weight	85 g	250 g
Battery	no	yes
Communication	USB	USB + Bluetooth
Auxiliary port	no	yes
Sensor connector	LEMO	LEMO + SPE ¹

See page 6 for system specifications.

software for Windows  and Android 



PSTrace for Windows provides support for all techniques and device functionalities.

PSTouch for Android supports all techniques supported by EmStat.

Minimum PC requirements for PSTrace: -Windows XP, Vista, 7, 8, or 10 (32-bit or 64-bit)
 -1 gigahertz (GHz) or faster 32-bit (x86) or 64-bit (x64) processor
 -1 gigabyte (GB) RAM (32-bit) or 2 GB RAM (64-bit).

See for more information: www.palmsens.com/software

¹ The SPE connector allows for direct insertion of the most popular types of Screen Printed Electrodes.

Supported techniques

The following techniques are supported by the EmStat series:

Voltammetric techniques

- | | |
|----------------------------------|-----|
| ▪ Linear Sweep Voltammetry | LSV |
| ▪ Differential Pulse Voltammetry | DPV |
| ▪ Square Wave Voltammetry | SWV |
| ▪ Normal Pulse Voltammetry | NPV |
| ▪ Cyclic Voltammetry | CV |

The above mentioned techniques can also be used for stripping voltammetry.

Techniques as a function of time

- | | |
|---|------|
| ▪ Amperometric Detection / | AD |
| Chronoamperometry | CA |
| ▪ Chronocoulometry | CC |
| ▪ Pulsed Amperometric Detection | PAD |
| ▪ Multiple Pulse Amperometric Detection | MPAD |
| ▪ Open Circuit Potentiometry | OCP |
| ▪ Multistep Amperometry | MA |

The current is measured using a **zero resistance ammeter (ZRA)**.

Where possible, the electrochemical techniques can be applied using **auto ranging** which means that the instrument automatically sets the optimal current range. The user can specify a highest and lowest current range in which the most appropriate range is selected automatically.

See page 5 for system specifications.

Specifications of general parameters

General pretreatment

Apply conditioning, deposition or begin potential for: 0 – 1600 s

General voltammetric parameters

Potential range for EmStat3: -3.000 V to +3.000 V

Potential range for EmStat3+: -4.000 V to +4.000 V

Step potential: 0.125 mV to 250 mV

Pulse potential: 0.125 mV to 250 mV

Limits of some technique specific parameters for EmStat3 and EmStat3+

NPV and DPV:	Scan rate:	0.025 mV/s (0.125 mV step) to 50 mV/s (5 mV step)
	Pulse time:	5 ms to 300 ms
SWV¹:	Frequency:	1 Hz to 500 Hz ¹
LSV and CV:	Scan rate:	0.01 mV/s (0.1 mV step) to 5 V/s (5 mV step)
AD:	Interval time:	1 ms to 300 s
	Run time:	1 s to hours
PAD:	Interval time:	50 ms to 300 s
	Pulse time:	1 ms to 1 s
	Run time:	10 s to hours
MPAD:	Pulse times:	100 ms to 2 s
	Run time:	10 s to hours
	Number of potential levels:	3
Potentiometry at open circuit (OCP):	Interval time:	1 ms to 30 s
	Maximum run time:	hours
Multistep Amperometry:	Interval time:	1 ms to 30 s
	Number of potential levels:	1 to 255
	Number of cycles:	1 to 20000
	Maximum run time:	hours

¹ PStace provides the option to measure forward and reverse currents separately.

Note: some limits of parameters are set for practical reasons and can be modified on request.

System specifications

	EmStat ³ [™]	EmStat ³⁺ [™]
▪ dc-potential range	± 3.000 V	± 4.000 V
▪ compliance voltage	± 5 V	± 8 V
▪ applied dc-potential resolution	0.1 mV	0.125 mV
▪ applied potential accuracy	≤ 0.2 % max. 2 mV offset	≤ 0.3 % max. 3 mV offset
▪ meas. potential resolution	1 mV	1 mV
▪ meas. potential accuracy	≤ 0.1 %, max 2 mV offset	≤ 0.1 %, max 2 mV offset
▪ current ranges	1 nA to 10 mA (8 ranges)	1 nA to 100 mA (9 ranges)
▪ maximum measured current	± 20 mA typical and ± 15 mA minimum	± 100 mA typical

EmStat 3 and 3+

▪ current resolution	0.1 % of current range 1 pA on lowest current range
▪ current accuracy	≤ 1 % of current range at 1 nA ≤ 0.5 % at 10 nA ≤ 0.2 % at 100 nA to 100 uA ≤ 0.5 % at 1 mA, 10 mA and 100 mA all with max. 0.2 % offset error
▪ electrometer amplifier input	> 100 Gohm // 4 pF
▪ rise time	approx. 100 µs
▪ sensor connection	shielded cable with circular connector for WE, RE, CE and Sense ²

EmStat 3 and 3+ regular model

▪ housing	anodized aluminium: 6.7 cm x 5.0 cm x (1.9 to 2.8 cm)
▪ weight	85 g
▪ power supply	USB 5 V, min. 130 mA (ES3) or 500 mA (ES3+)
▪ communication	USB
▪ auxiliary port	not present

EmStat 3 and 3+ Blue model

▪ housing	anodized aluminium: 100 mm x 60 mm x (27 to 34 mm)
▪ weight	250 g
▪ temperature range	0° C to +40° C
▪ power supply	USB or internal Li-Po battery 5 V, min. 130 mA (ES3) or 500 mA (ES3+)
▪ battery life	> 6 hours, connected via Bluetooth, cell on at 1mA current can be extended to >24 hours with external power bank full battery charge takes approx. 3 hours
▪ communication	USB or Bluetooth
▪ auxiliary port	D-Sub15 (female DE-15) with following pins available: - analog input and output (0 - 4.096 V, 12 bit) - 4 digital outputs, 1 digital input (5 V) - Rx / Tx (TTL) - 5 V output (max. 50 mA), digital and analog ground

² Only available for EmStat3+ to be used with 100 mA range.

Standard EmStat configuration

The Emstat regular model comes in a carrying case size 230 x 200 x 50 mm.

The case includes:

- EmStat3 or EmStat3+
- Mini-USB cable
- Sensor cable
- Croc clips
- Test sensor

Also included:

- PSTrace software + manual
- Quick start document

Standard EmStat Blue configuration

The Emstat Blue model comes in a carrying case size 230 x 200 x 70 mm.

The case includes:

- EmStat 3 or 3+ Blue
- Mini-USB cable
- Sensor cable
- Croc clips
- Test sensor

Also included:

- PSTrace software + manual
- Quick start document

Optional:

- 7" tablet
- Tablet charger



EmStat3 Blue in standard carrying case showing optional tablet



Differential Electrometer Amplifier (DEA)

The Differential Electrometer Amplifier (DEA) is a general purpose input amplifier. It can be used as a floating voltage amplifier with differential input and single output to the auxiliary port of EmStat Blue.

Default range is -5V to 5V (1x gain). Possible gains are: 2x, 5x, 10x, 20x, 50x, 100x, etc.

EmStat: Embedded Potentiostat for OEM purposes



EmStat as OEM module

The EmStat PCB's are also available as bare module for OEM purposes.

See for more information:

<http://www.palmsens.com/en/embedded-oem/>

Please do not hesitate to contact PalmSens for more details:
info@palmsens.com

PalmSens BV
The Netherlands
www.palmsens.com

DISCLAIMER

Changes in specifications and typing errors preserved.
Every effort has been made to ensure the accuracy of this document. However no rights can be claimed by the contents of this document.